



VISUAL CONTACT OUTSIDE



COLD-CUT, CRUSH-CUT OR  
ULTRASONIC



FLAME RETARDANT



MANUFACTURED IN THE EU  
REACH COMPLIANT



INDOOR AIR QUALITY  
CERTIFIED



ENVIRONMENTAL PRODUCT  
DECLARATION AVAILABLE

EPD registration number S-P-01098 [www.environdec.com](http://www.environdec.com)

TECHNICAL PROPERTIES		
Fabric Characteristic	Standard	
Composition		80 % PVC + 20 % PES
Weight (g/m <sup>2</sup> )		377 ± 5 %
Openness factor (%)		Approximately 10 %
Thickness (mm)		0.59 ± 5 %
Light fastness	EN ISO 4892-2 (exterior) (grey scale level)	5 4 White
Light fastness	EN ISO 105 B02:2002 (interior) (blue scale level)	8 7 White
Tearing resistance (daN)	EN ISO 13937-3:2001	Warp: 5.4 Weft: 5.5
Breaking strength (daN/5cm)	EN ISO 13934-1:1999	Warp: 116.2 Weft: 125.2
Stretch (%)	EN ISO 13934-1:1999	Warp: 18.9 % Weft: 17.8 %
Fire classification	NFPA 701	Pass
Roll size		250 cm width, 23.5 m length
Recycled content		2% Pre-consumer
Antibacterial activity	ASTM 2180-018	Microorganism growth inhibition




Roller blinds



Panel blinds



Skylight blinds

<b>Environmental &amp; health properties</b>	<b>Greenguard Gold</b> low VOC emission
<b>Manufacturing properties</b>	<p>Always store rolls horizontally  Cold-cut, crush-cut or ultrasonic  Welding: Thermo or ultrasonic  Manufacturing direction: Blinds can be manufactured 'drop to length' or railroded. BUT do not place manufactured in different directions in the same area, as this difference will be spotted.</p> <p>↓ →  Manufacture panel blinds only 'drop to length' ↓</p>
<b>Maintenance</b>	<p>Periodic maintenance: remove dust with a vacuum cleaner, dry cloth or compressed air  In case of accumulated dirt, it can be cleaned using a sponge or soft brush dipped in soapy water or spray cleaner. In both cases the fabric should be rinsed, leaving the curtain to dry open.  Under no circumstances should solvents or abrasives that could damage the fabric coating be used, so care should be taken to avoid paint, varnish or ink stains.</p> <div style="text-align: right;">  </div>

<b>Range of colours 2022</b>
Snow White
Navajo White
Capuccino
Graphite

*All specifications are based on average values and may deviate. The values are given for guidance and are not contractual. Subject to technical modifications*

**vertisol**

VERTISOL INT'L SRL  
C/Galileo Galilei, 68  
08403 Granollers  
SPAIN  
T: + 34 93 840 1444  
www.vertisol.com



ISO 9001:2015 and  
ISO 14001:2015  
certified company